

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1 Product identifier: GRUNT DO TWORZYW SZTUCZNYCH

## 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Additive for priming plastic parts.

Uses advised against: All uses not specified in this section or in section 7.3

## 1.3 Details of the supplier of the safety data sheet:

Agencja Handlowa "BOLL" Wojciech Dalewski Spólka Jawna ul. Chemiczna 3 65-713 Zielona Góra - Polska Phone.: 68 451 99 99 - Fax: 68 451 99 00 technolog@boll.pl

#### 1.4 Emergency telephone number:

#### SECTION 2: HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302 Asp. Tox. 1: Aspiration hazard, Category 1, H304 Flam. Liq. 2: Flammable liquids, Category 2, H225 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

## 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

Danger



#### Hazard statements:

H225 - Highly flammable liquid and vapour

H302+H332 - Harmful if swallowed or if inhaled

- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness
- H361d Suspected of damaging the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure

#### **Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P280: Wear protective gloves/protective clothing/eye protection

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P314: Get medical advice/attention if you feel unwell

P405: Store locked up

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substance:

Non-applicable

## 3.2 Mixture:

#### Chemical description: Mixture composed of organic substances

### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification		
		Toluene <sup>(1)</sup>	ATP CLP00	
	203-625-9 601-021-00-3 :01-2119471310-51-XXXX		Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	40 - <50 %
CAS:	1330-20-7	Xylene <sup>(1)</sup>	ATP CLP00	
EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	40 - <50 %	

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

## SECTION 4: FIRST AID MEASURES

## 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

## By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

## By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

#### SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:



## SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

## 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

## 7.2 Conditions for safe storage, including any incompatibilities:



#### SECTION 7: HANDLING AND STORAGE (continued)

## A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

Maximum time: 24 Months

## B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification		Environmental limits			
Toluene		IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>	
CAS: 108-88-3	EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>	
Xylene		IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>	
CAS: 1330-20-7	EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>	

## DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	369 - 399 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	369 - 399 mg/m <sup>3</sup>	369 - 399 mg/m <sup>3</sup>	177 - 207 mg/m <sup>3</sup>	177 - 207 mg/m <sup>3</sup>
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	165 - 195 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	274 - 304 mg/m <sup>3</sup>	274 - 304 mg/m <sup>3</sup>	62 - 92 mg/m <sup>3</sup>	Non-applicable

### DNEL (General population):

		Short e	xposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	-6,87 - 23,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	211 - 241 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	211 - 241 mg/m <sup>3</sup>	211 - 241 mg/m³	41,5 - 71,5 mg/m <sup>3</sup>	41,5 - 71,5 mg/m <sup>3</sup>
Xylene	Oral	Non-applicable	Non-applicable	-13,4 - 16,6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	93 - 123 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	-0,2 - 29,8 mg/m	<sup>3</sup> Non-applicable
PNEC:					
Identification					
Toluene	STP	-1,39 - 28,61 mg/L	Fresh water	-1	4,32 - 15,68 mg/L
CAS: 108-88-3	Soil	-12,11 - 17,89 mg/kg	Marine water	-14	4,32 - 15,68 mg/L
EC: 203-625-9	Intermittent	-14,32 - 15,68 mg/	L Sediment (Fresh	water) 1,3	39 - 31,39 mg/kg
	Oral	Non-applicable	Sediment (Marine	e water) 1,3	39 - 31,39 mg/kg
Xylene	STP	-8,42 - 21,58 mg/L	Fresh water	-1	4,67 - 15,33 mg/L
CAS: 1330-20-7	Soil	-12,69 - 17,31 mg/kg	Marine water	-14	4,67 - 15,33 mg/L
EC: 215-535-7	Intermittent	-14,67 - 15,33 mg/	L Sediment (Fresh	water) -2	,54 - 27,46 mg/kg
	Oral	Non-applicable	Sediment (Marine	e water) -2	,54 - 27,46 mg/kg



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

## 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

#### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 FN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2002	<b>0</b> +	DIN 12 899 ISO 3864-1:2002
Emergency shower		Eyewash stations	

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Revised: 18/06/2018 Version: 2 (Replaced 1)



1	Information on basic physical and chemica	Il properties:	
	For complete information see the product datash		
	Appearance:		
	Physical state at 20 °C:	Liquid	
	Appearance:	Fluid	
	Colour:	Colourless	
	Odour:	Characteristic	
	Odour threshold:	Non-applicable *	
	Volatility:		
	Boiling point at atmospheric pressure:	122 °C	
	Vapour pressure at 20 °C:	1943 Pa	
	Vapour pressure at 50 °C:	Non-applicable *	
	Evaporation rate at 20 °C:	Non-applicable *	
	Product description:		
	Density at 20 °C:	869 kg/m³	
	Relative density at 20 °C:	0,869	
	Dynamic viscosity at 20 °C:	Non-applicable *	
	Kinematic viscosity at 20 °C:	Non-applicable *	
	Kinematic viscosity at 40 °C:	<20,5 cSt	
	Concentration:	Non-applicable *	
	pH:	Non-applicable *	
	Vapour density at 20 °C:	Non-applicable *	
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *	
	Solubility in water at 20 °C:	Non-applicable *	
	Solubility properties:	Insoluble in water	
	Decomposition temperature:	Non-applicable *	
	Melting point/freezing point:	Non-applicable *	
	Explosive properties:	Non-applicable *	
	Oxidising properties:	Non-applicable *	
	Flammability:		
	Flash Point:	>4 °C	
	Flammability (solid, gas):	Non-applicable *	
	Autoignition temperature:	Non-applicable *	
	Lower flammability limit:	Not available	
	Upper flammability limit:	Not available	
	Explosive:		
	Lower explosive limit:	Non-applicable *	
	Upper explosive limit:	Non-applicable *	
2	Other information:		
	Surface tension at 20 °C:	Non-applicable *	
	Refraction index:	Non-applicable *	

SECTION 10: STABILITY AND REACTIVITY



### SECTION 10: STABILITY AND REACTIVITY (continued)

## 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

## 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

## 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

## 10.5 Incompatible materials:

[	Acids	Water	Combustive materials	Combustible materials	Others
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

## 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

## **11.1** Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- B- Inhalation (acute effect):
  - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
    - IARC: Toluene (3); Xylene (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Suspected of damaging the unborn child.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

#### Other information:

Non-applicable

## Specific toxicology information on the substances:

Identification	Acut	te toxicity	Genus
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	

#### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11.5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-625-9	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae

## 12.2 Persistence and degradability:

Identification	Degi	radability	Biodegradability	
Toluene	BOD5	2.5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %

### 12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential		
Toluene		BCF	13	
CAS: 108-88-3		Pow Log	2.73	
EC: 203-625-9		Potential	Low	
Xylene		BCF	9	
CAS: 1330-20-7		Pow Log	2.77	
EC: 215-535-7		Potential	Low	



## SECTION 12: ECOLOGICAL INFORMATION (continued)

## 12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		Volatility	
Toluene	Кос	178	Henry	672,8 Pa·m³/mol	
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes	
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes	
Xylene	Кос	202	Henry	524,86 Pa·m <sup>3</sup> /mol	
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes	
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes	

# 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous	

## Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity, HP10 Toxic for reproduction

## Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

	14.2	UN number: UN proper shipping name: Transport hazard class(es): Labels:	UN1263 PAINT 3 3
	14.4	Packing group:	II
3	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of da	ngero	us goods by sea:	



SECTION 14: TRANSPOR	ECTION 14: TRANSPORT INFORMATION (continued)				
With regard to IMDO	With regard to IMDG 38-16:				
14	.1 UN number:	UN1263			
14	.2 UN proper shipping name:	PAINT			
14	.3 Transport hazard class(es):	3			
	Labels:	3			
	.4 Packing group:	II			
3 14	.5 Environmental hazards:	No			
14	.6 Special precautions for user				
	Special regulations:	367, 163			
	EmS Codes:	F-E, S-E			
	Physico-Chemical properties:	see section 9			
	Limited quantities:	5 L			
	Segregation group:	Non-applicable			
14	7.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable			
Transport of dang	erous goods by air:				
With regard to IATA	ICAO 2018:				
14	.1 UN number:	UN1263			
14	.2 UN proper shipping name:	PAINT			
	.3 Transport hazard class(es):	3			
	Labels:	3			
3 14	.4 Packing group:	II			
14	.5 Environmental hazards:	No			
14	.6 Special precautions for user				
	Physico-Chemical properties:	see section 9			
14	.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable			

## SECTION 15: REGULATORY INFORMATION

15.1	15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:						
	Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable						
	Substances i	ncluded in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicabl	e				
	Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable						
	Article 95, REGULATION (EU) No 528/2012: Non-applicable						
	REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable						
Seveso III:							
	Section	Description	Lower-tier requirements	Upper-tier requirements			
	P5c		5000	50000			

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):



### Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: - metallic glitter intended mainly for decoration, - artificial snow and frost, "whoopee" cushions, — silly string aerosols, imitation excrement, horns for parties, - decorative flakes and foams, - artificial cobwebs, stink bombs. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'. Shall not be used in: -ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtravs. -tricks and jokes, -games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

SECTION 15: REGULATORY INFORMATION (continued)

## 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

## Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:** Non-applicable

#### Texts of the legislative phrases mentioned in section 2:

- H225: Highly flammable liquid and vapour
- H332: Harmful if inhaled

H302: Harmful if swallowed

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

H373: May cause damage to organs through prolonged or repeated exposure

H304: May be fatal if swallowed and enters airways

H361d: Suspected of damaging the unborn child.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



SECTI	ON 16: OTHER INFORMATION (continued)
	Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure STOT SE 3: H336 - May cause drowsiness or dizziness
	Classification procedure:
	Flam. Liq. 2: Calculation method (2.6.4.3) Acute Tox. 4: Calculation method Acute Tox. 4: Calculation method Skin Irrit. 2: Calculation method STOT SE 3: Calculation method STOT RE 2: Calculation method Asp. Tox. 1: Calculation method Repr. 2: Calculation method
	Advice related to training:
1	Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.
	Principal bibliographical sources:
I	http://echa.europa.eu http://eur-lex.europa.eu
	Abbreviations and acronyms:
	ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LC50: Effective concentration 50 Log-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Revised: 18/06/2018

Date of compilation: 03/02/2016

Version: 2 (Replaced 1)